


# Polypropylene Fitting Disconnect Assembly with EPDM for 3/8-in ID Tube, Installed - 12012

## Product Images

---



## Short Description

---

- Custom disposal can polypropylene fitting
- Polypropylene with EPDM disconnect assembly

## Description

---

Custom Quick-Disconnect Disposal Cans can be designed with up to eight fittings. You select the size, fitting material and position, and O-ring seal material to meet your needs. A minimum of two disconnect fittings are required, one intake and one vent. Unless otherwise specified, vent fitting on all cans will be the same as intake fitting.

Stainless Steel Fitting for 1/4-in (6mm) ID tubing: Based on your application choose polytetrafluoroethylene (PTFE), Viton® or EPDM seals with 1/4-in (6mm) flow.

Stainless Steel Fitting for 3/8-in (10mm) ID tubing: Based on your application choose polytetrafluoroethylene (PTFE), Viton® or EPDM seals with 1/4-in (6mm) flow.

Polypropylene Fitting for 3/8-in (10mm) ID tubing: This fitting is equipped with EPDM seals with 1/4-in (6mm) flow.

Suction Option Assembly: Internal 1/4-in (6mm) ID polytetrafluoroethylene (PTFE) tubing with stainless steel fitting is installed below disconnect (of your specification) to allow for safe dispensing of fluid out of the can.  
NOTE: must be used under suction only.

## Specifications

---

|                         |              |
|-------------------------|--------------|
| Model No                | 12012        |
| UPC                     | 697841062962 |
| Brand                   | Justrite     |
| International Model No. | 12012        |
| Net Weight, lbs         | 0.8          |
| Net Weight, kg          | 0.4          |