


Stainless Steel Fitting Disconnect Assembly with Viton for 1/4-in ID Tube, Installed - 12015

Product Images



Short Description

- Custom disposal can stainless steel fitting
- Stainless steel with Viton disconnect assembly

Description

Custom Quick-Disconnect Disposal Cans can be designed with up to eight fittings. You select the size, fitting material and position, and O-ring seal material to meet your needs. A minimum of two disconnect fittings is required, one intake and one vent. Unless otherwise specified, vent fitting on all cans will be the same as intake fitting.

Stainless Steel Fitting for 1/4-in (6mm) ID tubing: Based on your application choose polytetrafluoroethylene (PTFE), Viton® or EPDM seals with 1/4-in (6mm) flow.

Stainless Steel Fitting for 3/8-in (10mm) ID tubing: Based on your application choose polytetrafluoroethylene (PTFE), Viton® or EPDM seals with 1/4-in (6mm) flow.

Polypropylene Fitting for 3/8-in (10mm) ID tubing: This fitting is equipped with EPDM seals with 1/4-in (6mm) flow.

Suction Option Assembly: Internal 1/4-in (6mm) ID polytetrafluoroethylene (PTFE) tubing with stainless steel fitting is installed below disconnect (of your specification) to allow for safe dispensing of fluid out of the can.
NOTE: must be used under suction only.

Specifications

Model No	12015
UPC	697841062993
Brand	Justrite
International Model No.	12015
Net Weight, lbs	0.8
Net Weight, kg	0.4