

# Single Cylinder Hand Truck, 10.5" Pneumatic Wheels, Rear Casters - 35006

## Product Images



## Short Description

- Configured with 10.5-in (267-mm) steel hub pneumatic wheels with dual ball bearings for easier rolling—less effort required
- Includes wide-set dual 3-in (5-mm) swivel caster assemblies for easier, stable transport—folds flat for storage
- Rated at 1000-lb (454-kg) weight capacity
- Holds one cylinder from 6- to 12-in (155- to 305-mm) in diameter

## Description

Due to their weight, high-pressure contents, and unwieldy shape, industrial gas cylinders require a specially

designed hand truck to minimize accidents and injuries. Constructed of 1-in (25-mm) and 1.25-in (32-mm) diameter steel tube with continuous welding, these hand trucks provides optimum safety, strength and longevity. Robust, v-shaped cylinder support cradles keep cylinder snug and secure, reducing cylinder rolling common in curved back designs. Durable 1.5- x 54-in (38-mm x 1372-mm) polypropylene support straps, lab tested to 1138-lb (516-kg), feature steel cinch buckle and hold individual cylinders securely for safe transport.

Heavy-duty, 11-gauge (3-mm) floor plate with safety fins prevent warping or breaking. Features unique zero-lift height loading, allowing floor plate to lay flat, thereby eliminating the need to lift cylinder during loading and unloading. Caster carriage features heavy steel bars and nylon washers for smooth folding action and easy storage in tight spaces. Corrosion-resistant powder-coat finish throughout for long life and smooth handling. Upper handle sections bolt in place for reduced package size in order to save on freight costs.

Helps comply with OSHA, NFP1, NFPA 55, and CGA.

## Specifications

|                                         |                                    |
|-----------------------------------------|------------------------------------|
| Model No                                | 35006                              |
| UPC                                     | 697841209589                       |
| Brand                                   | Justrite                           |
| Cylinder Capacity                       | 1                                  |
| Minimum Cylinder Diam (in)              | 6                                  |
| Cylinder Capacity with Max Cylinder Dia | (1) 12 inch                        |
| Rear Casters                            | Yes                                |
| Rear Casters (inch)                     | 3                                  |
| Rear Casters (mm)                       | 76                                 |
| Main Wheel Type                         | Pneumatic                          |
| Main Wheel Size (inch)                  | 10.5                               |
| Main Wheel Size (mm)                    | 267                                |
| Weight Capacity (lb)                    | 1000                               |
| Weight Capacity (kg)                    | 454                                |
| Strap Style                             | Poly Cinch Strap with Steel Buckle |
| Straps Per Cylinder                     | 1                                  |
| Material Specifications                 | Steel                              |
| Complies with NFPA 1 Fire-Code          | Yes                                |
| NFPA 55                                 | Yes                                |
| OSHA Compliance                         | Yes                                |
| CGA                                     | Yes                                |
| Net Weight, lbs                         | 46                                 |
| Net Weight, kg                          | 21                                 |
| Net Dimensions (W x D x H)              | 21 x 19 x 47 inches                |
|                                         | 533 x 483 x 1194 mm                |