

Wall Mount, Hughes Handheld Eye/Face Wash, (2) 45-Degree Nozzles - OPT500

Product Images



Short Description

HUGHES



Justrite Safety Group

- Fitted with pop-off dust covers, a non-return valve and flow regulator
- Complete with 4.9-feet (1.5-m) of reinforced hose, particularly useful for treating disabled personnel
- Lock-on actuating button for ease of use

Description

Wall mounted hand-held eye/face wash features 45 degree angled double nozzles for hazardous environments where there is a risk of small spillages of chemicals or dangerous substances. Meets ANSI and EN 15154 water flow standards for an eye/face wash. Includes an inspection record tag for recording test and service history.

Specifications

Model No	OPT500
Color	Multicolor
UPC	805042000144
Brand	Justrite
Net Weight, lbs	2.2
Net Weight, kg	1
Dimensions, Exterior	13.4" H x 5.9" W x 5.4" D
Dimensions, Exterior	341mm H x 149mm W x 149mm D
Water Inlet Size NPT	1/2 in (F) - Hose
Minimum Operating Pressure	1.5 bar g, 22 PSI
Maximum Operating Pressure	6 bar g, 87 PSI
Water Flow Eye/Face Liters/min	11.4
Water Flow Eye/Face US Gal/min	3
Material Specifications	Body: Polyarylamide (reinforced with glass fibers), Nozzles: Powder coated brass, Eye Cups: EPDM
Operating Valve Material	Non-return
Mounting Type	Wall
Activation Method	Squeeze grip operated with lock-on actuating button
Minimum Ambient Temperature, °F	41
Minimum Ambient Temperature, °C	5
Maximum Ambient Temperature, °F	95
Maximum Ambient Temperature, °C	35