

317 Gallon, Hughes Emergency Tank Shower with Eye/Face Wash, Galvanized Steel Frame, 110V GP - QS1200

Product Images



Short Description

HUGHES



Justrite Safety Group

- Rectangular hollow section galvanized steel frames are earthquake-proof and conform to the California Building Code
- Internally mounted, covered eye/face wash unit protects against dust and debris
- Low-pressure shower rose delivers large quantities of water in an even pattern that is non-injurious to the user
- External water level indicator provides visibility to tank levels
- Ready for quick delivery—packed for economical shipment and assembly on-site

Description

Emergency tank showers are essential to providing safe working conditions where insufficient water pressure exists or when it is impractical to use a plumbed safety shower. The 317 gallon (1200 liter) model provides tepid water even when there is no mains water supply. An integral immersion heater, 110V general purpose rated, controlled by a dual safety thermostat, maintains the water in the insulated tank at a constant tepid temperature. In an emergency, the shower activates quickly with a simple push of the panic bar. Intended for use in applications within a temperature range of 14°F(-10°C) to 104°F(40°C). Assembly required.

Electrical supply: 110V Single Phase, 60/50Hz

Note: This tank shower is ANSI compliant for the 15 minute time requirement only when connected to a plumbed water source.

Specifications

Model No	QS1200
Color	Multicolor
UPC	805042000830
Brand	Justrite
Net Weight, lbs	750
Net Weight, kg	340
Filled Weight, lbs	2644
Filled Weight, kg	1198
Dimensions, Exterior	139" H x 67" W x 61" D
Dimensions, Exterior	3531mm H x 1702mm W x 1702mm D
Water Inlet Size NPT	3/4 in (F) and
Minimum Operating Pressure	0.5 bar g, 8 PSI
Maximum Operating Pressure	10 bar g, 145 PSI
Water Flow Shower/Body Liters/min	76
Water Flow Shower/Body US Gal/min	20
Water Flow Eye/Face Liters/min	11.4
Water Flow Eye/Face US Gal/min	3
Operating Valve Material	Shower Valve: UPVC, Eyewash: Stainless Steel
Eye/Face Wash Bowl Material	GRP Composite
Mounting Type	Floor
Pipework Material	UPVC and Stainless Steel
Activation Method	Shower: Push Bar, Eye/Face wash: Lift Lid Up
Eye/Face Wash Bowl Interior Dimensions	14" W x 7.5" D
	356mm W x 191mm D
Rose Diameter, inches	10.5
Rose Diameter, mm	264

Minimum Ambient Temperature, °F	14
Minimum Ambient Temperature, °C	-10
Maximum Ambient Temperature, °F	104
Maximum Ambient Temperature, °C	40
Electrical Equipment Classification	General Purpose
Electrical Supply	110 VAC, Single Phase, 60/50 Hz
Heating Type	Immersion Heater
Heating Load, Watts	1700
Operation Duration, min	13

Prop 65

⚠️WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.