



ANTI-VIBRATION CUT LEVEL 4 HIGH-DEXTERITY NITRILE DIPPED GLOVE

BEST VIBRATION PROTECTION.* HIGH DEXTERITY.

ISO 10819 | TRM=0.67 | TRH=0.52

ANTI-VIBRATION

CUT LEVEL 4

ANSI/ISEA 105



**SMARTWIPE™ Touch
Screen Compatible
Fingertips**

**Best Vibration
Reduction***

**Long-Lasting
Nitrile Dip**

*Compared to knit and dip anti-vibration gloves
when measuring transmission of the ISO 10819
vibration profile to the palm and fingers

EN388 STANDARDS

Abrasion	1	2	3	4	—	—
Cut Resistance (Coup Test)	1	2	2	4	5	X**
Tearing	1	2	3	4	—	—
Puncture	1	2	3	4	—	—
Cut Resistance (TDM Test)	A	B	C	D	E	F

**If the coupe test provides a 3 or above it is marked as an "X"
for not applicable and uses the TDM 100 test instead



**18 Gauge Knit
Total Mobility**

**TPR Knuckle
Protection**

**Light & Breathable
Design**

**Reinforced Nitrile Coating
Between thumb
and forefinger**



SPECIFICATIONS

Gauge	18
Liner Material	HPPE Blend Knit
Dip Material	Sandy Nitrile
Cuff Style	Elasticated Knit

RECOMMENDED APPLICATIONS

- Demolition
- Material Handling
- High Dexterity Applications
- General Work
- Automotive
- Remodeling
- Carpentry
- Tree Care

CARE INSTRUCTIONS

Machine wash warm water (105°F),
mild detergent, no bleach.
Line dry.

SIZE 1 PAIR

S	48-73-8760
M	48-73-8761
L	48-73-8762
XL	48-73-8763
XXL	48-73-8764

**SEE
MORE
PPE**



or visit <https://qr.mke.tl/2r2xz>

Milwaukee®

