

M8 male 0° A-cod. IDC

4-pol., 0,25 - 0,5mm², 2,5 - 5mm

Art.No.: 7000-08345-0000000

Weight: 0.008 kg

Country of origin: DE

Model designation: MSHL0-AC-T IDC 0,25-0,5mm²

IDC terminals



Male straight

M8, 4-pole


Connection cross section: 0.25...0.5 mm²

[Link to Product](#)

Illustration



Product may differ from Image



Side 1	
Family construction form	M8
No. of poles	4
Coding	A

Gender	male
Mounting method	inserted, screwed
Cable outlet	straight
Material	PA
Material contact	Copper alloy
Degree of protection (EN IEC 60529)	IP67, IP65

Side 2

Mounting method	Field-wireable
-----------------	----------------

Commercial data

URL Webshop	https://shop.murrelektronik.com/7000-08345-0000000
GTIN	4048879784696
EU-Customs tariff number	85366990
US-Customs tariff number	8536694020
ECLASS-6.0	27279221
ECLASS-6.1	27260702
ECLASS-7.0	27440102
ECLASS-7.1	27440102
ECLASS-8.0	27440102
ECLASS-8.1	27440102
ECLASS-9.0	27440116
ECLASS-9.1	27440106
ECLASS-10.0.1	27440106
ECLASS-10.1	27440102
ECLASS-11.0	27440106
ECLASS-11.1	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440106
ECLASS-14.0	27440106
ETIM-5.0	EC002635
ETIM-6.0	EC002635
ETIM-7.0	EC002635
ETIM-8.0	EC002635
ETIM-9.0	EC002635
ETIM-10.0	EC002635
customs tariff number	85366990
EAN	4048879784696
Packaging unit	1

Electrical data | Supply

Operating voltage AC	30 V
Operating voltage DC	30 V
Current operating per contact max.	4 A

Installation

Connection cross section min.	0,25 mm²
Connection cross section max.	0,5 mm²

Installation | Connection

Connection	Cut clamps IDC
Mating cycles min.	100
Wire insulation diameter min.	1,1 mm
Wire insulation diameter max.	1,55 mm

Device protection | Electrical

Additional condition protection degree	inserted, screwed
--	-------------------

Pollution Degree	3
Overvoltage category (EN 60950-1)	II
Insulation resistance min.	100 mΩ

Mechanical data | Material data

Material contact carrier	TPU
Coating contact	gold plated
Locking material	Zinc die-casting
Coating locking	Nickeled
Gasket	NBR

Mechanical data | Mounting data

Mounting method	Hexagonal screw, Hexagonal nut
Looking techniques	Schraubgewinde
Clamping range min.	2,5 mm
Clamping range max.	5 mm

Environmental characteristics | Climatic

Operating temperature min.	-25 °C
Operating temperature max.	80 °C

Important installation notes

Note on bending radius	Attention: Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces.
Note on strain relief	Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.

Conformity

Product standard	EN/IEC 61076-2-104 (M8)
------------------	-------------------------