

Date 10/11/2023
For the attention of:
Reference
Operator



ANGLED/CABINET UNIT COOLERS

Type: FHA 21 N 50

N. units: 1

Refriger (u) 2023 Ver. 2.3.1.394 - PRICE LIST 1/1/2023

Inlet air temp. (room)	[°C]	-8,0
Room relative humidity	[%]	85
Refrigerant		R448A
Altitude	[m]	0
Residual static pressure	[Pa]	0
DT1 needed for unit cooler (Dew)	[K]	8,0
Connection	230V-1PH-50Hz	EC FANS
Actual capacity	[W]	1.280
Air flow	[m3/h]	600,0
Air throw	[m]	9
Outlet air temperature	[°C]	-12,6
Evaporating temp (Dew)	[°C]	-16,0
DT superheating (Dew)	[K]	5,0
Temp. before expansion valve	[°C]	22,5
DT1 (Dew)	[K]	8,0
DTmlg	[K]	5,4
Fluid pressure drop	[K]	1,0
RC factor (Sensible capacity/Total capacity)	[%]	83,0
Energy efficiency class		A
Fan motor consumpt.	[W]	17
Power draw	[A]	0,14
Max fan absorbed current*	[A]	0,18
Fan speed	[1/min]	1400
Sound pressure level (5 m) 5	[dB(A)@5m]	42
Sound Power Level	[dB(A)]	67
N° Fans	[mm]	1 x 275
Poles	[n]	EC FANS
Fin spacing	[mm]	4,5
Internal volume	[dm3]	0,6
Surface	[m2]	3,8
Max Working pressure	[bar]	24,0
Casing material	Safeshell plastic material, white	Fin material Al
Header material	Cu	Tube material Cu
Weight	[kg]	9
Connections in	[n] x [mm]	1 x 12
Connections out	[n] x [mm]	1 x 10
Drain tray connection	["]	3/4
Overall dimensions	[mm]	615 x 555 x 260

(2014 thresholds)

(Fixed speed)



* Refer to LU-VE S.p.A. instruction manuals for details, data and standards. Noise level in 5m free field. The current may increase according to temperature frost quantity, external static pressure. The weight and dimensions are not valid for all possible configurations. All fans are ErP 2015-compliant (Directive 2009/125/EC Energy-related products). LU-VE S.p.A. reserves the right to modify and correct at any time, with or without notice, the specifications and prices listed in the Refriger software.

EUROVENT – CERTIFY ALL! Eurovent certification guarantees thermal performance, sound specifications, electrical power consumption, air volume flows. The certified performances and conditions in this software are in line with performances and conditions published on EUROVENT website.

LU-VE Group participates in the ECP programme for HE. Check ongoing validity of certificate and performance on www.eurovent-certification.com. The EUROVENT certification refers to the unit in standard configuration, additional options may impact on declared reference performance.

Accessories:

Q.ty	Code	Type:	Description
1	30196987	EC FAN - 230V - 1400rpm	EC FANS



Date	22-06-2015	Type:	FHA 21 N 50
Scale	1:1	Code:	10145786
			

Standard unit without accessories. For the connections please refer to the data sheet.