


# Rittal – The System.

Faster – better – everywhere.



## AX 1016.000

## Basic enclosure AX, stainless steel

State: 7/23/2026 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# AX 1016.000 - Basic enclosure AX, stainless steel

The robust stainless steel housings feature an integrated cam system that allows for extensive system expansion without drilling, quickly and securely.



## Features

|                                     |                                                                                                                                                     |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Model No.                           | AX 1016.000                                                                                                                                         |
| Material                            | Housing: Stainless steel<br>Door: Stainless steel, all-round foamed-in PU seal<br>Mounting plate: Carbon steel<br>Stainless steel 1.4301 (AISI 304) |
| Surface finish                      | Housing and door: Brushed, grain 400, peak-to-valley height < 0.8 µm<br>Mounting panel: Zinc-plated                                                 |
| Supply includes                     | Housing with door(s), swing angle 130°<br>Mounting panel<br>Lock: 3 mm double-bit                                                                   |
| Protection category NEMA            | NEMA 1<br>NEMA 3R<br>NEMA 4<br>NEMA 4X<br>NEMA 12                                                                                                   |
| Protection category IP to EN 60 529 | IP 66                                                                                                                                               |
| Type rating according to UL 50E     | Type 1<br>Type 3R<br>Type 4<br>Type 4X<br>Type 12                                                                                                   |

# Features

|                                      |                                                                                                                            |
|--------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| IK code                              | IK10                                                                                                                       |
| Dimensions                           | Width: 800 mm<br>Height: 1,000 mm<br>Depth: 300 mm<br>Width: 31.5 "<br>Height: 39.4 "<br>Depth: 11.8 "                     |
| Material thickness - door            | 2 mm<br>0.08 "                                                                                                             |
| Material thickness - enclosure       | 1.5 mm<br>0.06 "                                                                                                           |
| Material thickness – mounting plate  | 2.5 mm<br>0.1 "                                                                                                            |
| Dimensions of mounting plate (W x H) | 745 mm x 975 mm<br>29.3 " x 38.4 "                                                                                         |
| Number of doors                      | 1                                                                                                                          |
| Lock                                 | Lock version: Cam<br>No. of locks: 2<br>Lock Insert: 3 mm double-bit<br>Material lock: Die-cast zinc                       |
| Base material                        | Stainless steel 1.4301 (AISI 304)                                                                                          |
| Packaging unit                       | 1 pc(s).                                                                                                                   |
| Net weight                           | 50.3 kg                                                                                                                    |
| Gross weight                         | 51 kg                                                                                                                      |
| PCF/VE (cradle-to-gate)              | 172.68                                                                                                                     |
| Customs tariff number                | 94032080                                                                                                                   |
| ETIM 9                               | EC000261                                                                                                                   |
| ETIM 8                               | EC000261                                                                                                                   |
| ECLASS 8.0                           | 27180101                                                                                                                   |
| Product description                  | AX wall-mounted enclosure, WHD: 800x1000x300 mm, 304 stainless steel, with mounting panel, single-door, with two cam locks |

# Approvals

---

## Approvals

Bureau Veritas  
DNV  
Lloyds Register  
UL + C-UL (listed)

---

## Explanations

Declaration of conformity  
PCF-declaration