


Rittal – The System.

Faster – better – everywhere.



SZ 2433.010

Wall mounting bracket

State: 7/23/2026 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SZ 2433.010 - Wall mounting bracket for stainless steel AX

For mounting AX and KX stainless steel enclosures.

Features

Model No.	SZ 2433.010
Product description	For mounting AX and KX stainless steel housings.
Benefits	Simple location of the wall bracket on a pre-configured screw in the wall The wall mounting can be optimally adapted to the local conditions via various mounting positions If required, the holder can be fitted with a stylish cover cap
Material	Stainless steel 1.4301 (AISI 304)
Supply includes	Wall mounting bracket Cover Caps Assembly components
Wall distance	20 mm 0.79 "
Note	For hygiene reasons, and to retain the protection category, the stainless steel enclosures do not have any drilled holes for the wall-mounting brackets.
Suitable for	Enclosure type: AX stainless steel KX stainless steel
Type rating according to UL 50E	Type 1 Type 3R Type 4 Type 4X Type 12
Packaging unit	4 pc(s).
Net weight	0.4 kg
Gross weight	0.42 kg

Features

Customs tariff number	83025000
ETIM 9	EC002625
ETIM 8	EC002625
ECLASS 8.0	27189234
Product description	SZ Wall mounting bracket, for AX and KX, stainless steel 1.4301, wall distance: 20 mm

Approvals

Approvals	UL + C-UL - FTTA
-----------	------------------