

# Rittal – The System.

Faster – better – everywhere.



## SK 3342.230

## Rack-mounted fans for 482.6 mm (19")

State: 7/23/2026 (Source: [rittal.com/us-en](http://rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SK 3342.230 - Rack-mounted fans for 482.6 mm (19") Air throughput 188.34 - 282..52 cfm

Rack-mounted fan for direct installation in the 19" level. Installation allows air to circulate permanently inside the enclosure, which prevents the creation of hot spots.

## Features

|                                     |                                                                                                                                                                           |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model No.                           | SK 3342.230                                                                                                                                                               |
| Product description                 | Rack-mounted fan for direct installation in the 19" level. The installation enables permanent air circulation in the enclosure, which prevents the creation of hot spots. |
| Color                               | RAL 7035                                                                                                                                                                  |
| Supply includes                     | Wired unit ready for connection<br>Incl. terminal strip and assembly components                                                                                           |
| Air throughput (unimpeded air flow) | 480 m³/h<br>282.5 cfm                                                                                                                                                     |
| Rated operating voltage             | 230 V, 1~, 50 Hz/60 Hz                                                                                                                                                    |
| Rated current max.                  | At 50 Hz: 0.36 A<br>At 60 Hz: 0.33 A                                                                                                                                      |
| Pre-fuse                            | Miniature circuit-breaker/fuse: 6 A                                                                                                                                       |
| Dimensions                          | Width: 482.6 mm<br>Height: 44 mm<br>Depth: 200 mm<br>Width: 19 "<br>Height: 1.73 "<br>Depth: 7.87 "                                                                       |
| Distance between fan axes           | 105 mm<br>4.13 "                                                                                                                                                          |
| Number of fans                      | 3                                                                                                                                                                         |
| Noise pressure level                | At 50 Hz: 51 dB(A)                                                                                                                                                        |
| Operating temperature range         | -10 °C...55 °C<br>14 °F...131 °F                                                                                                                                          |

# Features

|                       |                                                                                                 |
|-----------------------|-------------------------------------------------------------------------------------------------|
| Packaging unit        | 1 pc(s).                                                                                        |
| Net weight            | 2.58 kg                                                                                         |
| Gross weight          | 2.743 kg                                                                                        |
| Customs tariff number | 84145915                                                                                        |
| ETIM 9                | EC000320                                                                                        |
| ETIM 8                | EC000320                                                                                        |
| ECLASS 8.0            | 27180716                                                                                        |
| Product description   | SK rack-mounted fan, for 482.6 mm (19), 282.5 cfm 230 V, 1~, 50/60 Hz, WHD: 482.6 x 44 x 200 mm |

# Approvals

|              |                               |
|--------------|-------------------------------|
| Approvals    | UR + C-UR (recognized)<br>VDE |
| Explanations | Declaration of conformity     |