

Rittal – The System.

Faster – better – everywhere.



VX 5301.312 Baying Connector

State: 7/23/2026 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



VX 5301.312 - Baying Connector for VX IT, TS IT

For baying enclosures from the VX IT series to TS IT.



Features

Model No.	VX 5301.312
Product description	For baying enclosures from the VX IT series to VX/TS/TS IT.
Material	Carbon steel
Surface finish	zinc-plated
Supply includes	4 baying connectors, exterior 2 baying connectors, interior Baying seal, 8 m Assembly components
Note	The maximum achievable IP protection category to IEC 60 529 is IP 54 To achieve the IP 54 protection class, the item "Baying cover on top for VX, TS" must also be used and a sealing strip must be attached.
Packaging unit	6 pc(s).
Net weight	1.14 kg
Gross weight	1.16 kg
PCF/VE (cradle-to-gate)	4.4 kg CO2 eq (Cat B)
Information regarding the PCF class	Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared
Customs tariff number	76169990
ETIM 9	EC002622

Features

ECLASS 8.0	27189263
Product description	Baying connector, for VX, VX IT/TS, TS IT, 4 baying connectors, external, 2 baying connectors, internal, baying seal, 8 m