

# Rittal – The System.

Faster – better – everywhere.



## SE 5852.600

## VX SE enclosure system

State: 7/23/2026 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SE 5852.600 - VX SE enclosure system Stainless steel

Individual stainless steel enclosure with stable enclosure body, two integrated mounting levels, screw-fastened rear panel and door. Roof and sides from a single piece with roll-formed frame. Fully compatible with the VX25 baying system. Enclosure widths ranging from 600 to 1200 mm. Increases efficiency as side panels do not have to be mounted.



## Features

|                 |                                                                                                                                                                                                                                                                                                                        |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model No.       | SE 5852.600                                                                                                                                                                                                                                                                                                            |
| Material        | Housing: Stainless steel 1.4301 (AISI 304), 1.5 mm, exterior brushed<br>Door: Stainless steel 1.4301 (AISI 304), 2.0 mm, exterior brushed<br>Rear panel: Stainless steel 1.4301 (AISI 304), 1.5 mm, exterior brushed<br>Base plates: Stainless steel 1.4301 (AISI 304), 1.5 mm<br>Mounting panel: Carbon steel, 3.0 mm |
| Surface finish  | Housing, door and rear panel: Brushed, grain 400<br>Base plates: Uncoated<br>Mounting panel: Zinc-plated                                                                                                                                                                                                               |
| Supply includes | Housing, solid top and sides<br>Door(s)<br>Right-hand door catch on single-door enclosures may be swapped to the left<br>Rear panel, detachable<br>Mounting panel<br>Base Plates<br>Lock: 3 mm double-bit<br>2 punched rails, 18 x 39 mm                                                                               |

# Features

|                                      |                                                                                                                                    |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Dimensions                           | Width: 800 mm<br>Height: 1,800 mm<br>Depth: 500 mm<br>Width: 31.5 "<br>Height: 70.9 "<br>Depth: 19.7 "                             |
| Dimensions of mounting plate (W x H) | 699 mm x 1,696 mm<br>27.5 " x 66.8 "                                                                                               |
| Protection category IP to EN 60529   | IP 55                                                                                                                              |
| Protection category NEMA             | NEMA 3R<br>NEMA 12                                                                                                                 |
| Type rating according to UL 50E      | Type 1<br>Type 2<br>Type 3<br>Type 3R<br>Type 12                                                                                   |
| IK code                              | IK10                                                                                                                               |
| Number of doors                      | 1                                                                                                                                  |
| Note                                 | Due to the hardness of the material, we recommend using metal multi-tooth screws 2486.400 for the interior installation.           |
| Base material                        | Stainless steel 1.4301 (AISI 304)                                                                                                  |
| Packaging unit                       | 1 pc(s).                                                                                                                           |
| Net weight                           | 119.85 kg                                                                                                                          |
| Gross weight                         | 125.35 kg                                                                                                                          |
| PCF/VE (cradle-to-gate)              | 384.75                                                                                                                             |
| Customs tariff number                | 94032080                                                                                                                           |
| ETIM 9                               | EC000261                                                                                                                           |
| ETIM 8                               | EC000261                                                                                                                           |
| ECLASS 8.0                           | 27180101                                                                                                                           |
| Product description                  | VX SE Free-standing enclosure system, WHD: 800x1800x500 mm, Stainless Steel, 1.4301, with mounting plate, single door at the front |

# Approvals

|              |                                                                              |
|--------------|------------------------------------------------------------------------------|
| Approvals    | UL + C-UL (listed)                                                           |
| Certificates | Surface finish<br>Protection category                                        |
| Explanations | Declaration of conformity<br>Declaration of conformity UK<br>PCF-declaration |