

# Rittal – The System.

Faster – better – everywhere.



## AX 6315.350

## Operating housing AX with handle strips

State: 7/23/2026 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# AX 6315.350 - Operating housing AX with handle strips

The command panel with handle strips based on AX, carbon steel, with support arm cut-out Ø 130 mm to match the support arm system CP 60/120/180, service access from front, aluminum front panel can be easily removed for machining, protection category IP55.



## Features

|                |                                                                                                                                                    |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Model No.      | AX 6315.350                                                                                                                                        |
| Version        | Support arm connection Ø 130 mm                                                                                                                    |
| Material       | Housing: Carbon steel<br>Door: Carbon steel, all-round foamed-in PU seal<br>Front panel: Aluminum<br>Cover caps: Plastic                           |
| Surface finish | Housing and door: Dipcoat primed, powder-coated on the outside, textured paint<br>Handle strip: Natural anodized<br>Front panel: Natural anodized. |
| General color  | RAL 7035                                                                                                                                           |
| Color          | Housing and door: RAL 7035<br>Handle strip: Natural anodized<br>Front panel: Natural anodized.<br>Cover caps: Similar to RAL 7024                  |

# Features

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply includes                 | <p>Housing with cut-out and reinforcement for support arm connection Ø 130 mm</p> <p>Front with maximum cut-out, covered with easily machinable 3 mm aluminum front panel</p> <p>Side handle strips with cover caps</p> <p>Integral interior mounting bracket with system punchings</p> <p>Cam lock with 3 mm double-bit insert</p>                                                                                                                                                     |
| Dimensions                      | <p>Width: 380 mm</p> <p>Height: 380 mm</p> <p>Depth: 210 mm</p> <p>Width: 15 "</p> <p>Height: 15 "</p> <p>Depth: 8.27 "</p>                                                                                                                                                                                                                                                                                                                                                             |
| Protection category NEMA        | <p>NEMA 1</p> <p>NEMA 12</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Type rating according to UL 50E | <p>Type 1</p> <p>Type 12</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Version                         | Service access from front                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| IK code                         | IK08                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Note                            | <p>The support arm connection and door catch may be swapped over by rotating the enclosure</p> <p>Optional: Support arm connection Ø 130 mm, preformed off-center in the reinforcement plate, easily drilled out</p> <p>Lock systems for servicing access from the rear: The lock insert may be exchanged for AX Mini Comfort Handle Type A 27 mm lock inserts</p> <p>Lock systems for servicing access from the front: Lock insert may be exchanged for 27 mm lock inserts, type A</p> |
| Base material                   | Carbon steel                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Note on Model No.:              | Compatible mounting plate 5051.371 with shipping bag 5051.300                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Packaging unit                  | 1 pc(s).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Net weight                      | 9.23 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Gross weight                    | 9.26 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| PCF/VE (cradle-to-gate)         | 40.7 kg CO2 eq (Cat B)                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

# Features

|                                     |                                                                                                                                     |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Information regarding the PCF class | Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared                |
| Customs tariff number               | 94032080                                                                                                                            |
| ETIM 9                              | EC002504                                                                                                                            |
| ETIM 8                              | EC002504                                                                                                                            |
| ECLASS 8.0                          | 27180505                                                                                                                            |
| Product description                 | AX Operating housing with handle strips, WHD: 380x380x210 mm, carbon steel, aluminum handle strips, servicing access from the front |

# Approvals

|              |                                                           |
|--------------|-----------------------------------------------------------|
| Approvals    | UL + C-UL (listed)                                        |
| Explanations | Declaration of conformity<br>Declaration of conformity UK |