


9002/22-032-300-111 Art. No. 158954



- For the intrinsically safe operation of a wide range of devices, such as HART transmitters, solenoid valves, sensors, potential-free contacts and many more
- Compact and space-saving devices that are easy to install on a DIN rail
- Quick to install as barriers can be simultaneously snapped onto the rail and connected to PE

MY R. STAHL 9002A



The series 9002 INTRINSPAK dual-channel safety barriers enable the intrinsically safe operation of virtually all field devices. The comprehensive portfolio and the combination of safety barriers cover a wide variety of signals. The devices are incredibly robust and require very little space. The back-up fuse is a convenient feature as it is standardised for all variants.

Technical Data

Explosion Protection	
Application range (zones)	2
Ex interface zone	0, 1, 2, 20, 21, 22
IECEEx gas certificate	IECEEx PTB 08.0057X
IECEEx gas explosion protection	Ex ec [ia Ga] IIC T4 Gc
IECEEx dust certificate	IECEEx PTB 08.0057X
IECEEx dust explosion protection	[Ex ia Da] IIIC
ATEX gas certificate	PTB 01 ATEX 2053 X
ATEX gas explosion protection	II 3 (1) G Ex ec [ia Ga] IIC T4 Gc
ATEX dust certificate	PTB 01 ATEX 2053 X
ATEX dust explosion protection	II (1) D [Ex ia Da] IIIC
FMus certificate	3010778
Marking FMus	NONINCENDIVE FOR, Class I, Div. 2, Groups A,B,C,D; T4; Class I, Zone 2, Group IIC T4 IS connections for Class I,II,III, Div. 1, Groups A,B,C,D,E,F,G; Class I, Zone 0, Groups IIC/IIB Hazardous location when inst. per doc. 90 026 11 31 1
Certificate ULus	E81680V1S3
Marking ULus	For use in Hazardous location, Class I, Div. 2, Groups A,B,C,D; T4 Providing IS circuits for Class I,II,III, GROUPS A,B,C,D,E,F,G; per doc. 90 026 11 31 3
Inmetro gas certificate	UL-BR 12.0354
Inmetro dust certificate	UL-BR 12.0354
Certificates	ATEX (PTB), Brazil (ULB), Canada (FM), IECEEx (PTB), India (PESO), Japan (CML), Korea (KGS), USA (FM), USA (UL)
Declaration of conformity	ATEX (EUK)
Installation	in Zone 2, Division 2 and in safe areas
Further information	See relevant certificate and operating instructions

9002/22-032-300-111 Art. No. 158954

Safety Data

Max. voltage U_o			1.6 V		
Max. current I_o			150 mA		
Max. power P_o			60 mW		
Max. permissible external capacity C_o for IIC			100 μ F		
Max. permissible external inductance L_o for IIC			1.3 mH		
Max. permissible external capacity C_o for IIB			1000 μ F		
Max. permissible external inductance L_o for IIB			7 mH		
Intrinsically safe limiting values Inductance L_o /capacitance C_o			Jointly connectable inductance L_o /capacitance C_o		
Channel 1	IIC	L_o [mH]	2 mH	1 mH	0.100 mH
		C_o [μ F]	20 μ F	29 μ F	73 μ F
	IIB	L_o [mH]	10 mH	1 mH	0.1 mH
		C_o [μ F]	72 μ F	200 μ F	640 μ F
Channel 2	IIC	L_o [mH]	2 mH	1 mH	0.1 mH
		C_o [μ F]	20 μ F	29 μ F	73 μ F
	IIB	L_o [mH]	10 mH	1 mH	0.1 mH
		C_o [μ F]	72 μ F	200 μ F	640 μ F
Channels 1 + 2	IIC	L_o [mH]		0.5 mH	0.10 mH
		C_o [μ F]		7.300 μ F	15 μ F
	IIB	L_o [mH]	2 mH	1 mH	0.1 mH
		C_o [μ F]	30 μ F	41 μ F	110 μ F

Electrical Data

Number of channels		2					
Type of voltage		AC/DC					
Maximum resistance R_{max}		20.1 Ω					
Minimum resistance R_{min}		19.9 Ω					
Maximum output current I_{max}		33 mA					
Potential channel 1		Alternative					
Potential channel 2		Alternative					
Transmission frequency channel 1		≤ 100 kHz					
I_{leak} leakage current for U_n		≤ 2 μ A					

Chan-nel	Nominal volt-age U_N	Maximum output current I_{max}	Minimum resist-ance R_{min}	Maximum resist-ance R_{max}	Maximum voltage U_o	Maximum current I_o	Maximum power P_o
1	0.70 V	33 mA	19.90 Ω	20.10 Ω	1.60 V	150 mA	60 mW
2	0.70 V	33 mA	19.90 Ω	20.10 Ω	1.60 V	150 mA	60 mW
1 + 2	1.40 V				3.20 V	300 mA	120 mW

Auxiliary Power

Power supply	Controlled
--------------	------------

Output

Temperature influence	$\leq 0,05$ %/10K
-----------------------	-------------------

Ambient Conditions

Ambient temperature	-20 °C ... +60 °C
---------------------	-------------------

9002/22-032-300-111 Art. No. 158954

Ambient Conditions

Ambient temperature	-4°F ... +140°F
Storage temperature	-20 °C ... +75 °C
Storage temperature	-4°F ... +167°F
Maximum relative humidity	95% average, no condensation



Mechanical Data

Degree of protection (IP)	IP40
Degree of protection (IP) terminals	IP20
Enclosure material	Polyamide 6GF
Number of connection terminals	4
Connection cross-section max.	1.5 mm ²
Connection cross-section AWG	16 AWG
Type of connection cable	Solid Finely stranded
Width	103 mm
Width, inches	4.09 in
Length	12 mm
Length in inches	0.48 in
Mounting depth	72 mm
Mounting depth in inches	2.76 in
Weight	110 g
Weight	0.24 lb

Mounting / Installation

Earthing connection cross-section	4 mm ²
Earthing conductor cross-section AWG	12 AWG
Connection type	2 PA
Min. torque, Nm	0.5 N · m
Min. torque, lb/in	4.43 lb/in
Max. torque, Nm	0.6 N · m
Max. torque, lb/in	5.31 lb/in

Technical Drawings – Subject to Alterations




Safety barriers


Two-channel safety barrier






9002/22-032-300-111 Art. No. 158954



Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



Accessories

Terminal block		Art. No.
	Phoenix Contact terminal block UT 4-PE	113057
	Phoenix Contact terminal block UT 6-PE	113058
Adaptor		Art. No.
	The adaptor enables a safety barrier to be installed on a clamping base (Art. No. 165283) or mounting plate from a previous series.	158826
Clamping base, moulded material		Art. No.
	Enables the safety barrier to be mounted on a G-rail. The safety barrier is mounted using the adaptor (Art. No. 158826).	165283

Safety barriers


Two-channel safety barrier

STAHL

9002/22-032-300-111 Art. No. 158954


Fuse holder

Art. No.



The fuse holder is snapped onto the side of a safety barrier and can be equipped with up to five back-up fuses (replacement).


158834



Spare Parts

Back-up fuse

Art. No.



For all series 9001, 9002 and 9004 safety barriers
Packaging unit: 5 pieces

158964


Label carrier

Art. No.



Transparent cover for the label

158977



We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.